

# 2000 SERIES

## TECHNICAL DATA



**PAL ADHESIVE PRODUCTS Ltd**



Product datasheet Issue No 1 Issued Nov 2006

### **RA 2089 DOUBLE-SIDED POLYPROPYLENE TAPE WHITE GLASSINE PAPER LINER**

#### TECHNICAL DETAILS

#### TYPICAL VALUE

#### UNITS

|                                     |            |                  |         |
|-------------------------------------|------------|------------------|---------|
| Thickness, adhesive + carrier       |            | 0.085            | mm      |
| Release liner thickness             |            | 0.068            | mm      |
| 180 degree peel adhesion:           | Open side  | 1150             | N/m     |
|                                     | Liner side | 1000             | N/m     |
| Polyester loop tack:                | Open side  | 1100             | N/m     |
|                                     | Liner side | 1000             | N/m     |
| Liner release                       |            | 10 max.          | N/m     |
| Tensile strength                    |            | 2200             | N/m     |
| Elongation at break                 |            | 75               | %       |
| Service temperature                 |            | -15 to +75       | Deg. C. |
| Recommended application temperature |            | +5 to +25        | Deg. C. |
| Shear adhesion, 1Kg @ 23 deg. C.    |            | Greater than 100 | Hours   |
| Shelf life                          |            | 12               | Months  |

Test Methods: BS 7116

**.THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY  
ALL DATA IS BASED UPON AVERAGE VALUES THE PURCHASER SHALL BE RESPONSIBLE FOR  
.DETERMINING THE SUITABILITY OF THIS PRODUCT FOR HIS PURPOSES**



**PAL ADHESIVE PRODUCTS Ltd**

Units 6-8 Bescot Industrial Estate, Woden Road West  
Wednesbury. West Midlands. WS10 7SG  
Tel: 0121-526 5151 Fax: 0121-505 1487